



The Experts in Wood Care

All Conference® 350 One Coat Polyurethane Gym Finish

PRODUCT INFORMATION

Description: All Conference® 350 is a solvent-based polyurethane finish specially formulated for a one coat application on wood sport floors. This product is designed with very low VOCs to minimize the odor concerns & meet even the strictest guidelines. The high solids property of All Conference® 350 provides protection for your floor & high gloss with only one coat.

Caution- Floors may become slippery when wet. Use proper caution signs & remove spill or standing water immediately. This product is not recommended for exterior use.

Directions for Use:

Application for Recoat (refer to the Magee Procedure Guide for complete instructions)

1. Thoroughly sweep or dust mop the floor, scrape or remove gum or debris.
2. Dry abrade the floor with 100 grit screens & 175rpm swing machine.
3. Tack the floor with water & clean towels to remove all residue.
4. Allow to dry thoroughly.
5. Apply 1 coat of All Conference® 350 with a heavy weight T-bar applicator.
6. Allow 8-12 hours to dry (conditions may vary dry times).
7. Allow floor to cure 24-48 hours before opening to light traffic.
8. Allow a minimum of 5 days before opening to regular use.

Maintenance

1. Dust mop daily with Waterthane® Dust Mop Treatment.
2. Use Magee® Speed Mop weekly, or as needed, with No Streak Floor Cleaner.

Specifications:

Color: Light amber

Odor: Solvent

Solids: 56-58%

Viscosity(ASTM1545): D-E

Coverage Rate: 500 sq ft/gal

Cure Rate: 14 days

VOC: <350 g/l

Dry Time: 8-12 hours

Flash Point: <105°F

Shelf Life: 2 years

HMIS	Rating
Health	2
Flammability	2
Reactivity	0
Personal Protection	-

Keep Out Of Reach Of Children
For Commercial & Industrial Use Only