



The Experts in Wood Care

Champion Finish

PRODUCT INFORMATION

Description: **Champion Finish** is a high performance oil-modified urethane finish for wood sport floors. This product is designed to provide durability, gloss & chemical resistance all at an economical price. **Champion Finish** can also be used to seal bare wood.

Caution- Floors may become slippery when wet. Use proper caution signs & remove spill or standing water immediately. This product is not recommended for exterior use.

Directions for Use:

Application for Recoat (refer to the Magee Procedure Guide for complete instructions)

1. Thoroughly sweep or dust mop the floor, scrape or remove gum or debris.
2. Dry abrade the floor with 100 grit screens & 175rpm swing machine.
3. Tack the floor with water & clean towels to remove all residue.
4. Allow the floor to dry thoroughly.
5. Apply **Champion Finish** with a **K-200 EZ Way Applicator** or a heavy weight T-bar applicator.
6. Allow 8-12 hours to dry (conditions may vary dry time, ensure floor is tack-free before proceeding with the next coat).
7. If more than 24 hours elapsed after 1st coat, dry abrade the floor & tack with water.
8. Apply the 2nd coat of **Champion Finish** & allow to dry.
9. Allow floor to cure 24-48 hours before opening to light traffic.
10. Allow a minimum of 5 days before opening to regular use.

Maintenance

1. Dust mop daily with **Waterthane® Dust Mop Treatment**.
2. Use **Magee® Speed Mop** weekly, or as needed, with **No Streak Floor Cleaner**.

Specifications:

Color: Light amber

Odor: Solvent

Solids: 34-36%

Viscosity(ASTM1545): A4-A5

Cure Rate: 14 days

VOC: 551g/l

Coverage Rate: 500 sq ft/gal

Dry Time: 8-12 hours

Flash Point: <105°F

Shelf Life: 2 years

HMIS	Rating
Health	2
Flammability	2
Reactivity	0
Personal Protection	-

Keep Out Of Reach Of Children
For Commercial & Industrial Use Only