



The Experts in Wood Care

Cure-O-Thane™ Sealer

PRODUCT INFORMATION

Description: Cure-O-Thane™ Sealer is a premium performance oil-modified urethane finish for wood sport floors. This product is designed to provide superior durability, high gloss & excellent chemical resistance. Cure-O-Thane™ Sealer is light in color and has excellent clarity to help your floor maintain a high appearance throughout the year.

Caution- Floors may become slippery when wet. Use proper caution signs & remove spill or standing water immediately. This product is not recommended for exterior use.

Directions for Use:

Application on bare maple for new or freshly sanded floors (refer to the Magee Procedure Guide for complete instructions)

1. Screen the floor with 100 grit screen.
2. Vacuum & tack with **Magee® Wood Kleen** until all residue is removed.
3. Allow the floor to dry thoroughly.
4. Apply **Cure-O-Thane™ Sealer** with a **K-200 EZ Way Applicator** or a heavy weight T-bar applicator.
5. Allow 3-6 hours to dry (conditions may vary dry time, ensure floor is tack-free before proceeding with the next coat).
6. After the 2nd coat, screen with the 120 grit screens, tack with **Magee® Wood Kleen** and allow to dry thoroughly.
7. Apply line markings if needed, and finish with 2 coats of a **Magee® OMU** finish.
8. Allow floor to cure 24-48 hours before opening to light traffic.
9. Allow a minimum of 5 days before opening to regular use.

Maintenance

1. Dust mop daily with **Waterthane® Dust Mop Treatment**.
2. Use **Magee® Speed Mop** weekly, or as needed, with **No Streak Floor Cleaner**.

Specifications:

Color: Light amber

Odor: Solvent

Solids: 29-31%

Viscosity(ASTM1545): A5-A4

Coverage Rate: 350-500 sq ft/gal

Dry Time: 3-6 hours

VOC: 593g/l

Flash Point: <105°F

Shelf Life: 2 years

HMIS	Rating
Health	2
Flammability	2
Reactivity	0
Personal Protection	-

Keep Out Of Reach Of Children
For Commercial & Industrial Use Only