



The Experts in Wood Care

## WATERTHANE® 400

### PRODUCT INFORMATION

**Description:** **Waterthane® 400** is a waterbased finish specially formulated for synthetic sports floors. Its unique blend of acrylic emulsion polymers and other ingredients allow for ease of application and long term film flexibility.

**Waterthane® 400** is a high gloss finish that will build gloss to a wet-look in as little as 2-3 coats. It will also respond to burnishing with high speed equipment to maintain a high level appearance throughout the year. If and when removal is required, **Waterthane® 400** can be removed with conventional floor strippers designed for synthetic sports floors.

**Caution-** Floors may become slippery when wet. Use proper caution signs & remove spill or standing water immediately. This product is not recommended for exterior use.

### Directions for Use:

#### Application

1. Strip the floor to remove old finish using a conventional floor stripper safe for synthetic sports floors. (Always follow product label instructions.)
2. After stripping, rinse well with water to remove all residue and allow to dry.
3. Apply **Waterthane® 400** with a **K-100 EZ Way Applicator** or a light weight T-bar.
4. Allow 45-60 minutes to dry, conditions may vary dry times so ensure floor is tack free before applying the next coat.
5. Apply 2-3 coats of finish until the desired appearance is achieved.

#### Maintenance

1. Dust mop daily with **Waterthane® Dust Mop Treatment**.
2. Use **Magee® Speed Mop** weekly, or as needed, with **No Streak Floor Cleaner**.

### Specifications:

Color: Opaque, off-white

Odor: Mild, ammonia

pH: 8.8

Solids: 15+/- 0.5%

Dry time: 45-60 minutes

Specific gravity: 1.02

Coverage rate: 2000-2500 sq ft/gal

Flash point: >200°F

Shelf life: 2 years

HMIS	Rating
Health	1
Flammability	0
Reactivity	0
Personal Protection	-

Keep Out Of Reach Of Children  
 Keep From Freezing  
 For Commercial & Industrial Use Only