



The Experts in Wood Care

WATERTHANE® 550

PRODUCT INFORMATION

Description: **Waterthane® 550** is a unique 2-part water-based urethane sanding seal for previously finished wood sports floors. This product is mixed with a crosslinker additive to give your floor exceptional hardness and durability. **Waterthane® 550** is versatile as it can be used as a sealer after a sand down, as a bridge coat over epoxy based finishes, or when switching from an OMU to a water-based finish.

Caution- Floors may become slippery when wet. Use proper caution signs & remove spill or standing water immediately. This product is not recommended for exterior use.

Directions for Use:

Application on bare maple for freshly sanded floors or as a tie-coat (refer to the Magee Procedure Guide for complete instructions)

1. Screen the floor with 100 grit screens & 175rpm swing machine.
2. Tack the floor with water & clean towels to remove all residue.
3. Apply **Waterthane® 550** with a **K-100 EZ Way** or a light weight T-bar applicator.
4. Allow 3-5 hours to dry, (conditions may vary dry time, so ensure floor is tack free before applying the next coat).
5. Abrade with a 3M maroon pad to remove the grain raise.
6. Tack with water until all residue is removed, allow to dry.
7. Apply the 2nd coat and repeat steps 5 & 6 before applying finish.
8. Apply 2-3 coats of **Magee®** finish until the desired appearance is achieved.
9. Allow floor to cure 24-48 hours before opening to moderate traffic.
10. Allow a minimum of 72 hours before opening to regular use.

Maintenance

1. Dust mop daily with **Waterthane® Dust Mop Treatment**.
2. Use **Magee® Speed Mop**, or as needed, with **No Streak Floor Cleaner**.

Specifications:

Color: Tan, slightly opaque

pH: 7.5-8.5

Odor: Mild, solvent

Solids: 24-26

VOC: <386 g/l (when mixed)

Dry time: 3-5 hours

Specific gravity: 1.06

Coverage rate: 350-700 sq ft/gal

Flash point: >200°F

Shelf life: 1 year

HMIS	Rating
Health	1
Flammability	0
Reactivity	0
Personal Protection	-

Keep Out Of Reach Of Children
Keep From Freezing
For Commercial & Industrial Use Only