



The Experts in Wood Care

WATERTHANE® 701 Satin

PRODUCT INFORMATION

Description: **Waterthane® 701 Satin** is a unique water-based oil-modified urethane satin finish for wood floors. It is specially formulated to give you the durability of an OMU finish, the low VOC & faster dry time like a water-based finish all with a satin finish. **Waterthane® 701 Satin** is extremely easy to use & does not require the addition of a crosslinker additive. It can be used on any wood floor to protect and maintain with a low gloss appearance.

Caution- Floors may become slippery when wet. Use proper caution signs & remove spill or standing water immediately. This product is not recommended for exterior use.

Directions for Use:

Application for Recoat (refer to the Magee Procedure Guide for complete instructions)

1. Thoroughly sweep or dust mop the floor, scrape or remove gum or debris.
2. Dry abrade the floor with 100 grit screens & 175rpm swing machine.
3. Tack the floor with water & clean towels to remove all residue.
4. Apply **Waterthane® 701 Satin** with a heavy weight T-bar applicator.
5. Allow 3-5 hours to dry, (conditions may vary dry time, so ensure floor is tack free before applying the next coat).
6. If more than 16 hours elapsed after 1st coat, dry abrade the floor & tack with water.
7. Allow floor to cure 24-48 hours before opening to moderate traffic.
8. Allow a minimum of 72 hours before opening to regular use.

Maintenance

1. Dust mop daily with **Waterthane® Dust Mop Treatment**.
2. Use **Magee® Speed Mop** weekly, or as needed, with **No Streak Floor Cleaner**.

Specifications:

Color: Opaque, off-white
 Odo-r: Mild, solvent
 pH: 8-9
 Solids: 23-25%
 Dry time: 3-5 hours
 Viscosity(ASTM1545): B-D
 Specific gravity: 1.0
 VOC: <185g/l
 Coverage rate: 600 sq ft/gal
 Flash point: >200°F
 Shelf life: 1 year

HMIS	Rating
Health	1
Flammability	0
Reactivity	0
Personal Protection	-

Keep Out Of Reach Of Children
 Keep From Freezing
 For Commercial & Industrial Use Only