



The Experts in Wood Care

WATERTHANE® 701

PRODUCT INFORMATION

Description: **Waterthane® 701** is a unique water-based oil-modified urethane finish for wood sports floors. It is specially formulated to give you the durability of an OMU finish and the low VOC & faster dry time like a water-based finish. **Waterthane® 701** is extremely easy to use & does not require the addition of a crosslinker additive. Enjoy the benefits of both worlds all at an economical price.

Caution- Floors may become slippery when wet. Use proper caution signs & remove spill or standing water immediately. This product is not recommended for exterior use.

Directions for Use:

Application for Recoat (refer to the Magee Procedure Guide for complete instructions)

1. Thoroughly sweep or dust mop the floor, scrape or remove gum or debris.
2. Dry abrade the floor with 100 grit screens & 175rpm swing machine.
3. Tack the floor with water & clean towels to remove all residue.
4. Apply **Waterthane® 701** with a light weight T-bar applicator.
5. Allow 3-5 hours to dry, (conditions may vary dry time, so ensure floor is tack free before applying the next coat).
6. If more than 16 hours elapsed after 1st coat, dry abrade the floor & tack with water.
7. Apply 2-3 coats of finish until the desired appearance is achieved.
8. Allow floor to cure 24-48 hours before opening to moderate traffic.
9. Allow a minimum of 72 hours before opening to regular use.

Maintenance

1. Dust mop daily with **Waterthane® Dust Mop Treatment**.
2. Use **Magee® Speed Mop**, or as needed, with **No Streak Floor Cleaner**.

Specifications:

Color: Opaque, light tan
 Odor: Mild, solvent
 pH: 8.0-9.0
 Solids: 26-28%
 Dry time: 3-5 hours
 Specific gravity: 1.01
 Viscosity(ASTM1545): A2-A
 VOC: <195g/l
 Coverage rate: 600 sq ft/gal
 Flash point: >200°F
 Shelf life: 1 year

HMIS	Rating
Health	1
Flammability	0
Reactivity	0
Personal Protection	-

Keep Out Of Reach Of Children
 Keep From Freezing
 For Commercial & Industrial Use Only