



Product Information

WOOD KLEEN

DESCRIPTION

WOOD KLEEN was formulated without water specifically for use on wood floors and wood surfaces. It is not a wood treatment, but a cleaner which will remove soil from wood surfaces without the use of soaps, detergents or water.

WOOD KLEEN is intended for use as a cleaner on wood floors and as a floor preparation prior to the sealing of gymnasium, racquetball courts and similar wood floors.

DIRECTIONS

DISPOSAL: Used product intended to be discarded is an ignitable hazardous waste as defined in RCRA (40 CFR261.21). Consult an authorized local waste handling company for disposal. The EPA Hazardous Waste Number is D001.

AS A CLEANER ON SEALED WOOD FLOORS

1. Damp mop floor using WOOD KLEEN as supplied.
2. On stubborn spots, use heel of mop.
3. Rubber burns, black marks, etc. may be spot cleaned with a cloth dampened with WOOD KLEEN.

PREPARING SEALED WOOD FLOORS FOR RECOATING

1. Clean floor of all water soluble soil by damp mopping with clear water. (Care must be taken not to warp the floor by allowing water to penetrate into the wood.)
2. Apply WOOD KLEEN and scrub the floor using a black stripping pad under a rotary machine. Move machine in a side to side motion at the pace of a slow walk. Be sure to overlap previously abraded areas by at least 1 to 2 inches.
3. Pick up excess soiled solution with a wet vac or towels. Refer to NOTE above for proper disposal.
4. Tack rag the floor with turkish towels dampened with WOOD KLEEN to remove any dust or residue.
5. Allow floor to dry and follow recommended recoating application technique of sealer or finish to be used.

CHEMICALLY STRIPPED FLOORS

Follow directions 2, 3, 4 and 5 above under Preparing Sealed Wood Floors for Recoating. (DO NOT clean floor with a water soluble cleaner.)

NEWLY SANDED FLOORS

1. Abrade the floor with a 120 grit screen.
2. Vacuum and tack rag the floor with turkish towels dampened with this product to remove any dust or residue.
3. Allow floor to dry and follow recommended application technique of sealer and finish to be used.

WARNING: Combustible. Contains Petroleum Distillate. Keep away from heat, sparks and all flames, including but not limited to pilot lights. Open doors and windows for cross-ventilation. Close container after each use. Cloths used with this product are combustible and should be discarded in closed metal containers placed outdoors. Harmful Or Fatal If Swallowed. Do not take internally. Eye And Skin Irritant. Avoid prolonged or repeated contact with skin.

FIRST AID: If swallowed, do not induce vomiting. Call a physician immediately. If in eyes, flush thoroughly with water for at least 15 minutes, then see a doctor. For skin, wash with soap and water. If irritation persists, see a doctor.

Keep Out Of Reach Of Children · For Industrial & Institutional Use Only

SPECIFICATIONS

| | | | |
|---------------------------|------------------------------|---------------------------------|---------------------------------------------------|
| Type product | Waterless wood floor cleaner | Viscosity (Gardner-Holdt) | A-5 |
| Appearance | Water white | Percent active | 100 |
| Odor | Moderate low | Weight per gallon | 6.46 lbs. |
| Solvency | Kauri-Butanol value 33 | Residue | None |
| Evaporation rate | 0.12 (butyl acetate = 1) | Flash point (T.C.C.) | 105° F |
| Spontaneous heating | None | Coverage | For cleaning and tacking - 500 sq. ft. per gallon |